


### EMC contact strip



To ensure EMC protection when horizontal rails are set-back. Integral channel to accommodate EMC gaskets.

**Material:**  
Extruded aluminum section, clear-chromated

**Note:**  
2 sections are required for each subrack.


**EMC**

U	Packs of	Order No.
3	1	<b>3684.643</b>
6	1	<b>3684.644</b>
9	1	<b>3684.645</b>

#### ! Also required:

EMC gaskets, vertical, see page 116.  
Assembly screws M3 x 6, packs of 100, order no. 3684.233, see page 164

### EMC gaskets, horizontal (K)



For horizontal EMC protection. For snapfastening onto the front horizontal rails.

**Material:**  
Stainless steel

**European patent no. 0 937 375**  
**with validity for DE**  
**US patent no. 6,137,052**  
**Chinese patent**  
**no. ZL 97 1 98582.0**

**EMC**

Usable width (HP)	Packs of	Order No.
For top/bottom horizontal rail		
40	1	<b>3684.974</b>
84	1	<b>3684.808</b>
84	10	<b>3684.246</b>
When subdividing 6 U into 2 x 3 U, between 2 horizontal rails		
84	1	<b>3685.789</b>
84	10	<b>3685.229</b>

### EMC gaskets



**For covers**  
For EMC shielding between the horizontal rails and covers.

**Material:**  
Stainless steel

**EMC**

HP	Packs of	Order No.
84	10	<b>3684.245</b>

### Mounting blocks



For mounting covers, versions 1 – 4, on the subrack side panel.

**Material:**  
Die-cast zinc, nickel-plated

**Note:**  
For EMC applications, mounting blocks must be fitted across the entire subrack depth. The table here shows the number of mounting blocks required to install 1 cover plate with EMC shielding.

**EMC**

	Packs of	Order No.
Mounting blocks 28.5 mm each	10	<b>3684.234</b>

Number of mounting blocks for max. EMC protection	Depth of multi-level screening plate mm
4	142
8	192
10	212
12	252
14	272
16	312
18	332
20	372
24	432
28	492
32	552

#### ! Also required:

Assembly screws M3 x 6, packs of 100, order no. 3684.233, see page 164

