

Specification Sheet

Part Number: 118-00032



Article Number

118-00032

Type

PT2A

Color

Beige (BGE)

Features & Benefits

- Extreme temperature range for excellent performance in a range of environments.
- Low-profile, contoured head takes up less space and protects sensitive wires.
- Delivers the performance of a metal tie with the ease of use of plastic.

Quantity Per

bag

Product Description

PEEK Ties withstand temperatures from -67 to 464° F and provide excellent resistance to chemicals, acids, radiation and abrasion. The low-profile, contoured head takes up less space and protects sensitive wires running adjacent to it.

Short Description

High-Temp Cable Tie, 5.7" Long, 52lb Tensile Strength, PEEK, Beige, 100/pkg

Global Part Name

PT2A-PEEK-BGE

Minimum Tensile Strength (Imperial)

52.0

Minimum Tensile Strength (Metric)

230.0

Length L (Imperial)

5.7

Length L (Metric)

145.0

Identification Plate Position

none

Releasable Closure

No

Tie Closure

plastic pawl

Variant

Outside Serrated

Width W (Imperial)

0.13

Width W (Metric)

3.4

Bundle Diameter Min (Imperial)

0.16

Bundle Diameter Min (Metric)

4.0

Bundle Diameter Max (Imperial)

1.4

Bundle Diameter Max (Metric)

35.0

Thickness T (Imperial)

0.05

Thickness T (Metric)

1.2

Cable Tie Head Length (Imperial)	0.22
Cable Tie Head Width (Imperial)	0.24
Material	Polyetheretherketone (PEEK)
Material Shortcut	PEEK
Flammability	UL 94 V0
Halogen free	Yes
Operating Temperature (Metric)	-67°F to +464°F (-55°C to +240°C)
Reach Complaint(Article 33)	Yes
ROHS Complaint	Yes
Certification/Specification WEB	DNV GL EN 62275:2009 VDE DIN EN 62275:2010-07
Package Quantity(Imperial)	100
Package Quantity (Metric)	100
Customs Number	3926909987
Content Unit(BMEcat)	pcs.
Weight (Metric)	0.8

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)