


HDBaseT Class B (HDBaseT-Lite) HDMI over Cat5e/6/6a Extender Transceiver, Serial and IR, 4K x 2K @ 30 Hz UHD / 1080p @ 60 Hz, Up to 230 ft. (70 m), TAA

MODEL NUMBER: BHDBT-TR-SI



Transmits uncompressed HDMI video and audio, RS-232 serial and IR remote control signals over a single Cat5e/6/6a cable up to 230 ft. to projectors, monitors or televisions in a chain.

Description

Insert the BHDBT-TR-SI HDBaseT Class B (HDBaseT-Lite) HDMI over Cat5e/6/6a Extender Transceiver between the transmitter and receiver units in your Tripp Lite HDBaseT Class B installation to extend the range of your signal. Connect its HDMI port to a projector, monitor or television to expand your installation.

Using a single Cat5e/6/6a cable, the BHDBT-TR-SI transmits uncompressed HDMI audio and video, RS-232 serial and IR control signals up to 230 feet (70 m) from the previous unit in the chain (either the transmitter or another transceiver), including a 1920 x 1080 (1080p) signal @ 60 Hz. It can also extend an Ultra High Definition (UHD) 4096 x 2160 or 3840 x 2160 (4K x 2K) video signal up to 130 feet (40 m) from the previous unit in the chain. Add up to five BHDBT-TR-SI Extender Transceivers to the chain for a total range up to 780 feet (4K x 2K) or 1,380 feet (1080p) with a monitor connected to each transceiver.

RS-232 serial signals and IR remote control signals (@ 39 KHz) also pass through the transceiver, so your HDBaseT installation can control such RS-232 devices as scanners and touchscreen displays at baud rates up to 115 Kbps. You can also operate a Blu-ray player using its remote when at the remote monitor and vice versa. Locking HDMI ports (ideal for use with Tripp Lite's P569-006-LOCK High-Speed HDMI cables with locking connectors) prevent cables from coming loose or undone, ensuring an intact signal. Attach the BHDBT-TR-SI to a wall, rack or pole using the included hardware.

Features

Extends and Expands Your HDBaseT Class B (HDBaseT-Lite) Installation

Highlights

- Extends and expands your Tripp Lite HDBaseT Class B installation
- Connects multiple monitors at different links in a chain
- Extends both a 4096 x 2160 and 3840 x 2160 (4K x 2K) @ 30 Hz signal up to 130 feet (40 m)
- Extends a 1080p @ 60 Hz signal up to 230 feet (70 m)
- Supports 7.1-channel surround sound, DTS-HD and Dolby TrueHD

Package Includes

- BHDBT-TR-SI HDBaseT Class B HDMI over Cat5e/6/6a Extender Transceiver
- External Power Supply with NEMA 1-15P Plug (Input: 100–240V, 50/60 Hz, 0.5A; Output: 5V, 3A)
- Mounting hardware
- Owner's Manual



- Extends an Ultra High Definition (UHD) 4096 x 2160 or 3840 x 2160 (4K x 2K) @ 30 Hz signal up to 130 feet (40 m)
- Extends a High Definition 1920 x 1080 (1080p) @ 60 Hz signal up to 230 feet (70 m)
- Connects to next link in the chain with just one Cat5e/6/6a cable
- Add up to 5 transceivers to further expand the range of your installation up to 780 feet (4K x 2K) or 1,380 feet (1080p) with a monitor attached to each transceiver
- Supports 7.1-channel surround sound, DTS-HD and Dolby TrueHD audio
- Supports 36-bit Deep Color (12 bits per channel), CEC passthrough, 3D video, EDID and HDCP

Allows RS-232 and IR Control Passthrough

- Passes through RS-232 serial signals at 115 Kbps full-duplex baud rates for devices such as scanners and touchscreen monitors
- Passes through IR remote control signals so you can operate your Blu-ray player with its remote while standing at the remote monitor (and vice versa)

Easy to Set Up and Use

- Plug-and-play engineering—no software or drivers to download and install
- Inserts quickly between transmitter and receiver in Tripp Lite HDBaseT Class B installation
- Included mounting hardware lets you install each unit on a wall, rack or pole
- Locking HDMI ports (ideal for use with Tripp Lite's P569-006-LOCK HDMI cables) prevent cables from coming loose or disconnected, ensuring an intact signal

TAA-Compliant

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

| OVERVIEW | |
|---------------------------------|--|
| UPC Code | 037332187062 |
| AC Adapter | Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 3A |
| Technology | HDBaseT; HDMI (All types); Serial (RS232); IR |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 2.200 x 8.400 x 6.500 |
| Shipping Dimensions (hwd / cm) | 5.59 x 21.34 x 16.51 |
| Shipping Weight (lbs.) | 1.3400 |
| Shipping Weight (kg) | 0.61 |
| Unit Dimensions (hwd / in.) | 1.2 x 5 x 4 |



| | |
|--------------------------------------|---------------------------|
| Included Mounting Accessories | Y |
| Color | Black |
| Unit Weight Details | 1lb. |
| ENVIRONMENTAL | |
| Operating Temperature Range | 0 to 40 C (32 to 104 F) |
| Storage Temperature Range | -20 to 60 C (-4 to 140 F) |
| Relative Humidity | 20 to 90% |
| COMMUNICATIONS | |
| Max 1024 x 768 Range (ft) | 230 |
| Max 480P Range (ft) | 230 |
| Max 1440 x 900 Range (ft) | 230 |
| Max 1080i Range (ft) | 230 |
| Max 1080P Range (ft) | 230 |
| Max 1920 x 1440 Range (ft) | 130 |
| Max 2560 x 1600 Range (ft) | 130 |
| Max 4K UHD Range (ft) | 130 |
| Max 480i Range (ft) | 230 |
| Max 640 x 480 Range (ft) | 230 |
| Max 800 x 600 Range (ft) | 230 |
| Max 1600 x 1200 Range (ft) | 230 |
| Max 1920 x 1200 Range (ft) | 130 |
| Max 2048 x 1536 Range (ft) | 130 |
| Max 720P Range (ft) | 230 |
| CONNECTIONS | |
| Ports | 0 |
| Side A - Connector 1 | HDMI (FEMALE) |
| Side B - Connector 1 | (2) RJ45 (FEMALE) |
| FEATURES & SPECIFICATIONS | |
| IR Remote Extension Support | Yes |
| RS-232 Serial Extension Support | Yes |
| 10/100 Ethernet Extension Support | No |
| CERTIFICATIONS | |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|-------------------------------------|-------------------------|
| Approvals | CE, FCC, RoHS, REACH |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>