



| PANDUIT PART NO | BUNDLE DIAM | | A in (mm) | B in (mm) | C in (mm) | D in (mm) | E in (mm) | F in (mm) | LOOP TENSILE lbs (N) | CROSS SECTION | WEIGHT lbs(g)/100 pcs | TIP STYLE |
|-----------------|--------------|---------------|---------------|--------------|---------------|---------------|---------------|----------------|-------------------------|---------------|-----------------------------|-----------|
| | MIN in (mm) | MAX in (mm) | | | | | | | | | | |
| S4-18 | .06 (1.5) | .87 (22) | .044 (1.1) | .10 (2.5) | .19 (4.8) | .154 (3.9) | .181 (4.6) | 3.94 (100) | 18 (80) | MINIATURE | 0.054 (24.3) | CURVED |
| S6-18 | .06 (1.5) | 1.57 (40) | .044 (1.1) | .10 (2.5) | .19 (4.8) | .154 (3.9) | .188 (4.8) | 6.29 (160) | 18 (80) | MINIATURE | 0.100 (45.5) | CURVED |
| S8-18 | .06 (1.5) | 2.09 (53) | .045 (1.2) | .10 (2.5) | .19 (4.8) | .157 (4.0) | .19 (4.8) | 7.87 (200) | 18 (80) | MINIATURE | 0.124 (56.2) | CURVED |
| S6-40 | .08 (2.0) | 1.30 (33) | .045 (1.2) | .14 (3.6) | .26 (6.6) | .19 (4.8) | .268 (6.8) | 5.51 (140) | 40 (178) | INTERMEDIATE | 0.148 (67.4) | CURVED |
| S8-40 | .08 (2.0) | 2.09 (53) | .045 (1.2) | .14 (3.6) | .256 (6.5) | .19 (4.8) | .268 (6.8) | 7.87 (200) | 40 (178) | INTERMEDIATE | 0.195 (88.7) | CURVED |
| S12-40 | .08 (2.0) | 2.99 (76) | .045 (1.2) | .14 (3.6) | .26 (6.6) | .181 (4.6) | .264 (6.7) | 11.81 (300) | 40 (178) | INTERMEDIATE | .299 (135.9) | CURVED |
| S15-40 | .08 (2.0) | 4.02 (102) | .051 (1.3) | .14 (3.6) | .232 (5.9) | .181 (4.6) | .248 (6.3) | 14.57 (370) | 40 (178) | INTERMEDIATE | .377 (171.1) | CURVED |

NOTE:
SEE WWW.PANDUIT.COM FOR PART NUMBER SUFFIX DESIGNATION FOR PACKAGE SIZE, PART MATERIAL,
PART COLOR AND ANY THIRD PARTY RECOGNITION OR COMPLIANCE.

| REV | DATE | BY | CHK | APR | DESCRIPTION | ECN | TITLE | ITEM REVISION NAME | DATASET FILE NAME | MATERIAL: | DRAWING NUMBER: |
|-----|---------|-----|------|------|------------------|--------|--|------------------------|-------------------|----------------|-----------------|
| 00 | 3-15-17 | ACC | JSWA | JADE | DRAWING RELEASED | 012502 | STRONGHOLD MINIATURE AND INTERMEDIATE TIES | 00092FBI/00 | 00092FBI_DC/00 | NYLON 6.6 | 00092FBI_DC |
| | | | | | | | CUSTOMER DRAWING | | | PANDUIT | |
| | | | | | | | UNLESS OTHERWISE SPECIFIED, DIMENSIONAL TOLERANCES ARE: IN [mm] | | | | |
| | | | | | | | .x ± .1 [2.54] .xxx ± .020 [.51] | | | | |
| | | | | | | | .xx ± .02 [.5] ANGLES ± 5 ° | | | | |
| | | | | | | | | THIRD ANGLE PROJECTION | | | |
| REV | DATE | BY | CHK | APR | DESCRIPTION | ECN | DRAWN BY | DATE | CHK | SCALE | SIZE |
| | | | | | | | ACC | 2-22-17 | JSWA | N/A | A |
| | | | | | | | | | | | SHT 1 OF 1 |

D10100DA/20